

## BX10P



- ▶ Suitable for level adjustment and for uneven and porous surfaces such as cardboard, etc.
- ▶ In the two-coloured suction cup the bellows and the sealing lip are of different hardnesses, which makes the suction cup strong and stable and, at the same time, soft and flexible.
- ▶ DURAFLEX® suction cups manufactured in a specially developed material that features the elasticity of rubber and wear resistance of polyurethane.
- ▶ The material DURAFLEX® is mark free.

### Lifting forces & Technical data

Material	Lifting force vertical to the surface, N, at vacuum level			Lifting force parallel to the surface, N, at vacuum level			Volume cm <sup>3</sup>	Min. curve radius mm	Max. vertical movement mm	Weight rubber part g
	20 -kPa	60 -kPa	90 -kPa	20 -kPa	60 -kPa	90 -kPa				
PU30°/60°	1	2.3	3.7	—	—	—	0.56	4.0	4.5	1
PU60°	1	2.3	3.7	—	—	—	0.56	6.0	4.5	1

### Material specifications

Material	Colour	Hardness °Shore A	Temperature range °C
Polyurethane, PU30	Yellow transparent	30	10–50
Polyurethane, PU60	Green transparent	60	10–50


### Material resistance

Wear resistance	Oil	Weather & ozone	Hydrolysis	Petrol	Concentrated acids	Ethanol	Methanol	Oxidation
Excellent	Excellent	Excellent	Fair**	Fair	Fair**	Fair	Poor	Poor


\*\*Please contact Piab.

## Ordering information

Description	Art. No.
Suction cup BX10P Polyurethane 30/60, M5 male	0122869
Suction cup BX10P Polyurethane 60, M5 male	0122967



Rubber parts	Art. No.
Suction cup BX10P Polyurethane 30/60	0118329
Suction cup BX10P Polyurethane 60	0122966



Fittings	Art. No.
Fitting M5 male, 10-15	3107030