

# BX75P



### Suction cup with 21/2 bellows

- Suitable for level adjustment and for uneven and porous surfaces such as cardboard, etc.
- In the two-coloured suction cup the bellows and the sealing lip are of different hardnesses, which makes the suction cup strong and stable and, at the same time, soft and flexible.
- DURAFLEX® suction cups manufactured in a specially developed material that features the elasticity of rubber and wear resistance of polyurethane.
- ▶ The material DURAFLEX® is mark free.

## Lifting forces & Technical data

| Material  | Lifting force vertical to the surface, N, at vacuum level |         | Lifting force parallel to the surface, N, at vacuum level |         |         | Volume  | Min.<br>curve<br>radius | Max.<br>vertical<br>movement | Weight<br>rubber<br>part |    |
|-----------|---|---------|---|---------|---------|---------|-------------------------|------------------------------|--------------------------|----|
|           | 20 -kPa   | 60 -kPa | 90 -kPa   | 20 -kPa | 60 -kPa | 90 -kPa | cm <sup>3</sup>         | mm                           | mm                       | g  |
| PU30°/60° | 62  | 110     | 141   | 39*     | 83*     | 116*    | 80                      | 23.0                         | 26                       | 71 |
| PU60°     | 80  | 120     | 166   | 78*     | 114*    | 150*    | 80                      | 23.0                         | 26                       | 71 |

\*The suction cup is not intended for handling shear lifts. The values are given as a dimensioning guide to be used when, e.g., the acceleration/retardation causes shear forces.

### **Material specifications**

| Material           | Colour             | Hardness<br>°Shore A | Temperature range<br>°C |
|--------------------|--------------------|----------------------|-------------------------|
| Polyurethane, PU30 | Yellow transparent | 30                   | 10–50                   |
| Polyurethane, PU60 | Green transparent  | 60                   | 10–50                   |

### **Material resistance**


| We<br>resist |           | -        | leather<br>ozone | Hydrolysis | Petrol | Concentrated<br>acids | Ethanol | Methanol | Oxidation |
|--------------|-----------|----------|------------------|------------|--------|-----------------------|---------|----------|-----------|
| Exce         | lent Exce | llent Ex | kcellent         | Fair**     | Fair   | Fair**                | Fair    | Poor     | Poor      |


\*\*Please contact Piab.



#### **Ordering information**


|   | Complete suction cups   | Art. No.     |
|---|---|--------------|
| А | Suction cup BX75P Polyurethane 30/60, G3/8" male / 1/8" NPSF female             | 0106293      |
| А | Suction cup BX75P Polyurethane 30/60 with filter, G3/8" male / 1/8" NPSF female | 0106606      |
| В | Suction cup BX75P Polyurethane 30/60 with filter, thread insert G3/8" male      | 0107151      |
| В | Suction cup BX75P Polyurethane 60 with filter, thread insert G3/8" male         | 0107149      |
| С | Suction cup BX75P Polyurethane 30/60 with filter, 3/8" NPSF female              | 0108794      |
| С | Suction cup BX75P Polyurethane 60 with filter, 3/8" NPSF female                 | 0108795      |
|   |   | _3/8"-18NPSF |






<Picture\_Text changed="2004-04-27 10:49:37">A

<Picture\_Text changed="2004-04-27 10:49:57">B



13:46:52">C

| Rubber parts  | Art. No. |
|---|----------|
| Suction cup BX75P Polyurethane 30/60 with filter, for thread insert | 0107145  |
| Suction cup BX75P Polyurethane 60 with filter, for thread insert    | 0107150  |



| Fittings                              | Art. No. |
|---------------------------------------|----------|
| Thread insert G3/8" male, with O-ring | 0106797  |

| Spare Part       | Material      | Temperature range<br>°C | Art. No. |
|------------------|---------------|-------------------------|----------|
| Filter for BX75P | Polyester/TPE | -40-90                  | 0106374  |