SUCTION CUPS F



F15



FLAT SUCTION CUP WITH CLEATS

- ► Suitable for flat objects.
- ▶ Good stability and little inherent movement.
- ► Recommended when the lifting force is parallel to the surface of the object.
- ➤ Cleats prevent thin, sensitive objects from being deformed and gives extra friction when the lifting force is parallel.

LIFTING FORCES & TECHNICAL DATA

Lifting force vertical to the surface, N, at vacuum level		Lifting force parallel to the surface, N, at vacuum level			Volume	Min. curve radius	Max. vertical movement	Weight rubber part	
20 -kPa	60 -kPa	90 -kPa	20 -kPa	60 -kPa	90 -kPa	cm³	mm	mm	g
3.5	8.5	11.0	3.5	6.5	7.5	0.37	13	1.0	0.9

MATERIAL SPECIFICATIONS

Material	Colour	Hardness °Shore A	Temperature range °C
Chloroprene, CR	Black	50	-40–110
Silicone, SIL	Red	50	-40–200

MATERIAL RESISTANCE


Material	Wear resistance	Oil	Weather & ozone	Hydrolysis	Petrol	Concentrated acids	Alcohol	Oxidation
Chloroprene, CR	Excellent	Fair	Good	Good	Fair	Poor	Good	Good
Silicone, SIL	Good	Poor	Excellent	Fair	Poor	Poor	Good	Excellent

SUCTION CUPS F



ORDERING INFORMATION

Complete suction cups	Art. No.
Suction cup F15 Chloroprene, M5 male	3150014
Suction cup F15 Silicone, M5 male	3150014S



Rubber parts	Art. No.
Suction cup F15 Chloroprene	3150125
Suction cup F15 Silicone	3150125S



Fittings	Art. No.
Fitting M5 male, 10–15	3107030

For further information and dimensioned drawings, see SUCTION CUPS FITTINGS chapter.