

F25



Flat suction cup with cleats

- ▶ Suitable for flat objects.
- ▶ Good stability and little inherent movement.
- ▶ Recommended when the lifting force is parallel to the surface of the object.
- ▶ Cleats prevent thin, sensitive objects from being deformed and gives extra friction when the lifting force is parallel.

Lifting forces & Technical data

Lifting force vertical to the surface, N, at vacuum level			Lifting force parallel to the surface, N, at vacuum level			Volume	Min. curve radius	Max. vertical movement	Weight rubber part
20 -kPa	60 -kPa	90 -kPa	20 -kPa	60 -kPa	90 -kPa	cm ³	mm	mm	g
9.0	19.5	25	8.0	9.0	10.0	1.1	22	1.5	1.8

Material specifications


Material	Colour	Hardness °Shore A	Temperature range °C
Chloroprene, CR	Black	50	-40-110
Silicone, SIL	Red	50	-40-200

Material resistance


Material	Wear resistance	Oil	Weather & ozone	Hydrolysis	Petrol	Concentrated acids	Alcohol	Oxidation
Chloroprene, CR	Excellent	Fair	Good	Good	Fair	Poor	Good	Good
Silicone, SIL	Good	Poor	Excellent	Fair	Poor	Poor	Good	Excellent

Ordering information


	Complete suction cups	Art. No.
A	Suction cup F25 Chloroprene, M5 female	0101292
B	Suction cup F25 Chloroprene, G1/8" male, with mesh filter	0101293
B	Suction cup F25 Chloroprene, G1/8" male, with mesh filter and dual flow control valve	0101299
C	Suction cup F25 Chloroprene, G1/8" male/M5 female, with mesh filter	0101297
C	Suction cup F25 Chloroprene, G1/8" male/M5 female, with dual flow control valve	0101301
D	Suction cup F25 Chloroprene, 5xM5 female	0101296
A	Suction cup F25 Silicone, M5 female	0101303
B	Suction cup F25 Silicone, G1/8" male, with mesh filter	0101304
C	Suction cup F25 Silicone, G1/8" male/M5 female, with mesh filter	0101308
C	Suction cup F25 Silicone, G1/8" male/M5 female, with dual flow control valve	0101312
D	Suction cup F25 Silicone, 5xM5 female	0101307
E	Suction cup F25 Chloroprene, G1/8" male/M5 female, PA	0109842
E	Suction cup F25 Silicone, G1/8" male/M5 female, PA	0110335




<Picture_Text changed="2004-04-27 11:59:08">A




<Picture_Text changed="2004-04-27 11:59:23">B



<Picture_Text changed="2004-04-27 11:59:40">C




<Picture_Text changed="2004-04-27 11:59:57">D



<Picture_Text changed="2004-04-27 12:00:11">E

	Rubber parts	Art. No.
	Suction cup F25 Chloroprene	0101131
	Suction cup F25 Silicone	0101132



<Picture_Text changed="2004-07-05 08:40:16">

	Fittings	Art. No.
	Fitting M5 female	3250003
	Fitting M5 female, with dual flow control valve	3251001
	Fitting G1/8" male, with mesh filter	3250085
	Fitting G1/8" male, with mesh filter and dual flow control valve	3251002
	Fitting G1/8" male/M5 female, with mesh filter	0101152
	Fitting G1/8" male/M5 female, with dual flow control valve	3251004
	Fitting 5xM5 female	0100260
	Fitting 5xM5 female, with dual flow control valve	3251005
	Fitting G1/8" male/M5 female, PA	3150196