

## F40-2



### Flat suction cup with cleats

- ▶ Suitable for flat objects.
- ▶ Good stability and little inherent movement.
- ▶ Recommended when the lifting force is parallel to the surface of the object.
- ▶ Cleats prevent thin, sensitive objects from being deformed and gives extra friction when the lifting force is parallel.

### Lifting forces & Technical data

Lifting force vertical to the surface, N, at vacuum level			Lifting force parallel to the surface, N, at vacuum level			Volume cm <sup>3</sup>	Min. curve radius mm	Max. vertical movement mm	Weight rubber part g
20 -kPa	60 -kPa	90 -kPa	20 -kPa	60 -kPa	90 -kPa				
20.0	40	50	15.0	25	30	4.8	52	2.5	5.5

### Material specifications


Material	Colour	Hardness °Shore A	Temperature range °C
Nitrile-PVC, NPV	Black	50	0-90
Silicone, SIL	Red	50	-40-200

### Material resistance


Material	Wear resistance	Oil	Weather & Ozone	Hydrolysis	Petrol	Concentrated acids	Alcohol	Oxidation
Nitrile-PVC, NPV	Excellent	Excellent	Good	Good	Excellent	Fair	Good	Good
Silicone, SIL	Good	Poor	Excellent	Fair	Poor	Poor	Good	Excellent

### Ordering information


	Complete suction cups	Art. No.
A	Suction cup F40-2 Nitrile-PVC, 1/8" NPSF female, with mesh filter	0101572
A	Suction cup F40-2 Nitrile-PVC, 1/8" NPSF female, with dual flow control valve	0101573
B	Suction cup F40-2 Nitrile-PVC, G1/4" male, with mesh filter	0101567
B	Suction cup F40-2 Nitrile-PVC, G1/4" male, with mesh filter and dual flow control valve	0101574
C	Suction cup F40-2 Nitrile-PVC, G3/8" male, with mesh filter	0101569
C	Suction cup F40-2 Nitrile-PVC, G3/8" male, with mesh filter and dual flow control valve	0101576
D	Suction cup F40-2 Nitrile-PVC, 5x1/8" NPSF female	0101571
E	Suction cup F40-2 Nitrile-PVC, 1/8" NPSF female PA	0109847
F	Suction cup F40-2 Nitrile-PVC, 1/8" NPSF female, with cone valve	3150050P
A	Suction cup F40-2 Silicone, 1/8" NPSF female, with mesh filter	0101553
A	Suction cup F40-2 Silicone, 1/8" NPSF female, with dual flow control valve	0101554
B	Suction cup F40-2 Silicone, G1/4" male, with mesh filter	0101548
C	Suction cup F40-2 Silicone, G3/8" male, with mesh filter	0101550
D	Suction cup F40-2 Silicone, 5x1/8" NPSF female	0101552
E	Suction cup F40-2 Silicone, 1/8" NPSF female PA	0110345
F	Suction cup F40-2 Silicone, 1/8" NPSF female, with cone valve	3150050S




<Picture\_Text changed="2004-04-27 13:05:09">A




<Picture\_Text changed="2004-04-27 13:05:23">B




<Picture\_Text changed="2004-04-27 13:05:38">C



<Picture\_Text changed="2004-04-27 13:05:57">D




<Picture\_Text changed="2004-04-27 13:06:13">E



<Picture\_Text changed="2007-05-30 11:36:28">F

Rubber parts	Art. No.
Suction cup F40-2 Nitrile-PVC	0101135
Suction cup F40-2 Nitrile-PVC, for fitting with cone valve	3150240P
Suction cup F40-2 Silicone	0101136
Suction cup F40-2 Silicone, for fitting with cone valve	3150240S



Fittings	Art. No
Fitting 1/8" NPSF female, 30–40, with mesh filter	0101153
Fitting 1/8" NPSF female, 30–40, with dual flow control valve	3251006
Fitting 1/8" NPSF female, 30–40, with cone valve	0101156
Fitting G1/4" male, 30–40, with mesh filter	3250091
Fitting G1/4" male, 30–40, with mesh filter and dual flow control valve	3251007
Fitting G3/8" male, 30–40, with mesh filter	3250086
Fitting G3/8" male, 30–40, with mesh and dual flow control valve	3251009
Fitting 5x1/8" NPSF female, 30–40	0100261
Fitting 5x1/8" NPSF female, 30–40, with dual flow control valve	3251011
Fitting 1/8" NPSF female, 30–40, PA	3150197

Spare Part	Material	Temperature range °C	Art. No.
Cone valve for F40-2	Al/SS/NBR	-40–110	3150056