

F50-2



Flat suction cup with cleats

- ▶ Suitable for flat objects.
- ▶ Good stability and little inherent movement.
- ▶ Recommended when the lifting force is parallel to the surface of the object.
- ▶ Cleats prevent thin, sensitive objects from being deformed and gives extra friction when the lifting force is parallel.

Lifting forces & Technical data

Lifting force vertical to the surface, N, at vacuum level			Lifting force parallel to the surface, N, at vacuum level			Volume cm ³	Min. curve radius mm	Max. vertical movement mm	Weight rubber part g
20 -kPa	60 -kPa	90 -kPa	20 -kPa	60 -kPa	90 -kPa				
36	74	96	24.0	40	50	10	55	3.0	14

Material specifications

Material	Colour	Hardness °Shore A	Temperature range °C
Nitrile-PVC, NPV	Black	50	0–90
Silicone, SIL	Red	50	-40–200
HNBR	Grey-blue	75	-30–140*


* For a shorter period of time up to +160 °C

Material resistance


Material	Wear resistance	Oil	Weather & ozone	Hydrolysis	Petrol	Concentrated acids	Alcohol	Oxidation
Nitrile-PVC, NPV	Excellent	Excellent	Good	Good	Excellent	Fair	Good	Good
Silicone, SIL	Good	Poor	Excellent	Fair	Poor	Poor	Good	Excellent
HNBR	Excellent	Excellent	Excellent	Good	Excellent	Fair	Good	Excellent

Ordering information


	Complete suction cups	Art. No.
A	Suction cup F50-2 Nitrile-PVC, 1/8" NPSF female, with mesh filter	0101772
A	Suction cup F50-2 Nitrile-PVC, 1/8" NPSF female, with dual flow control valve	0101773
B	Suction cup F50-2 Nitrile-PVC, G1/4" male, with mesh filter	0101767
B	Suction cup F50-2 Nitrile-PVC, G1/4" male, with mesh filter and dual flow control valve	0101774
C	Suction cup F50-2 Nitrile-PVC, G3/8" male, with mesh filter	0101769
C	Suction cup F50-2 Nitrile-PVC, G3/8" male, with mesh filter and dual flow control valve	0101776
D	Suction cup F50-2 Nitrile-PVC, 5x1/8" NPSF female	0101771
D	Suction cup F50-2 Nitrile-PVC, 5x1/8" NPSF female, with dual flow control valve	0101778
E	Suction cup F50-2 Nitrile-PVC, 1/8" NPSF female, PA	0110952
F	Suction cup F50-2 Nitrile-PVC, 1/8" NPSF female, with cone valve	3150051P
A	Suction cup F50-2 Silicone, 1/8" NPSF female, with mesh filter	0101753
A	Suction cup F50-2 Silicone, 1/8" NPSF female, with dual flow control valve	0101754
B	Suction cup F50-2 Silicone, G1/4" male, with mesh filter	0101748
C	Suction cup F50-2 Silicone, G3/8" male, with mesh filter	0101750
D	Suction cup F50-2 Silicone, 5x1/8" NPSF female	0101752
E	Suction cup F50-2 Silicone, 1/8" NPSF female, PA	0110346
F	Suction cup F50-2 Silicone, 1/8" NPSF female, with cone valve	3150051S
A	Suction cup F50-2 HNBR, 1/8" NPSF female	0108181
B	Suction cup F50-2 HNBR, G1/4" male, with mesh filter	0108182
C	Suction cup F50-2 HNBR, G3/8" male, with mesh filter	0108183




<Picture_Text changed="2004-07-01 16:32:39">A




<Picture_Text changed="2004-07-01 16:32:03">B




<Picture_Text changed="2004-07-01 16:31:18">C



<Picture_Text changed="2004-07-01 16:31:31">D




<Picture_Text changed="2004-07-01 16:30:03">E



<Picture_Text changed="2007-05-30 11:40:44">F

Rubber parts	Art. No.
Suction cup F50-2 Nitrile-PVC	0101137
Suction cup F50-2 Nitrile-PVC, for fitting with cone valve	3150241P
Suction cup F50-2 Silicone	0101138
Suction cup F50-2 Silicone, for fitting with cone valve	3150241S
Suction cup F50-2 HNBR	0108166



Fittings	Art. No
Fitting 1/8" NPSF female, 50	3250017
Fitting 1/8" NPSF female, 50, with mesh filter	0101154
Fitting 1/8" NPSF female, 50, with dual flow control valve	3251012
Fitting 1/8" NPSF female, 50, with cone valve	0101157
Fitting G1/4" male, 50, with mesh filter	3250092
Fitting G1/4" male, with mesh filter and dual flow control valve	3251013
Fitting G3/8" male, 50, with mesh filter	3250087
Fitting G3/8" male, 50, with mesh filter and dual flow control valve	3251015
Fitting 5x1/8" NPSF female, 50	0100262
Fitting 5x1/8" NPSF female, 50, with dual flow control valve	3251017
Fitting 1/8" NPSF female, 50, PA	3150198

Spare Part	Material	Temperature range °C	Art. No.
Cone valve for F50-2	Al/SS/NBR	-40-110	3150057