

F50MF



Flat suction cup with cleats, mark free

- Suction cup of TPU, a mark free material that leaves no trace on the object being handled.
- Suitable for flat surfaces.
- ▶ Good stability and little inherent movement.
- Recommended when the lifting force is parallel to the surface of the object.

Lifting forces & Technical data

| | force vertica , N, at vacuu | | Lifting force parallel to the surface, N, at vacuum level | | Volume | Min. curve radius | Max. vertical movement | Weight rubber part | |
|---------|--------------------------------|---------|---|---------|---------|----------------------|------------------------------|--------------------------|----|
| 20 -kPa | 60 -kPa | 90 -kPa | 20 -kPa | 60 -kPa | 90 -kPa | cm³ | mm | mm | g |
| 24.5 | 92 | 141 | 31 | 82 | 107 | 10 | 95 | 2.0 | 10 |

Material specifications

| Material | Colour | Hardness °Shore A | Temperature range °C |
|---------------------------------|-------------------|----------------------|-------------------------|
| Thermoelastic polyurethane, TPU | Transparent white | 81 | -20–80 |

Material resistance

| Wear resistance | Oil | Weather & Ozone | Hydrolysis | Petrol | Concentrated acids | Alcohol | Oxidation |
|--------------------|-----------|--------------------|------------|--------|-----------------------|---------|-----------|
| Excellent | Excellent | Excellent | Poor | Poor | Poor | Good | Good |



Ordering information

| Complete suction cups | Art. No. |
|---|-------------------------------|
| A Suction cup F50MF Thermoelastic polyurethane, 1/8" NPSF female, with mesh filter | 0101791 |
| B Suction cup F50MF Thermoelastic polyurethane, G1/4" male, with mesh filter | 0101786 |
| B Suction cup F50MF Thermoelastic polyurethane, G1/4" male, with mesh filter and dual flow control valve | 0101793 |
| C Suction cup F50MF Thermoelastic polyurethane, G3/8" male, with mesh filter | 0101788 |
| $(Picture_Text changed="2004-04-27 14:21:58">A (Picture_Text changed="2004-04-27 14:22:13">B (Picture_Text changed="2004-04-27 14:22:29">C (Picture_Text changed="$ | |
| Rubber parts | Art. No. |
| Suction cup F50MF Thermoelastic polyurethane | 0101143 |
| <pre>Picture_Text changed="2004- 04-27 14:23:01"></pre> | |
| Fittings | Art. No |
| Fitting 1/8" NPSF female, 50, with mesh filter | 0101154 |
| Fitting 1/8" NPSF female, 50, with dual flow control valve | 3251012 |
| Fitting G1/4" male, 50, with mesh filter | 3250092 |
| Thung G1/4 Thate, 50, whit thesi filler | 3230032 |
| Fitting G1/4" male, so, with mesh filter and dual flow control valve | 3251013 |
| | |
| Fitting G1/4" male, with mesh filter and dual flow control valve | 3251013 |
| Fitting G1/4" male, with mesh filter and dual flow control valve Fitting G3/8" male, 50, with mesh filter | 3251013 3250087 |
| Fitting G1/4" male, with mesh filter and dual flow control valve Fitting G3/8" male, 50, with mesh filter Fitting G3/8" male, 50, with mesh filter and dual flow control valve | 3251013 3250087 3251015 |