

F75P



Flat suction cup with cleats

- ▶ Suitable for flat and rough surfaces.
- ▶ Fair stability and little inherent movement.
- ▶ Recommended when the lifting force is parallel to the surface of the object.
- ▶ In the two-coloured suction cup the bellows and the sealing lip are of different hardnesses, which makes the suction cup strong and stable and, at the same time, soft and flexible.
- ▶ DURAFLEX® suction cups manufactured in a specially developed material that features the elasticity of rubber and wear resistance of polyurethane. The material does not leave any marks on the objects handled.

Lifting forces & Technical data

Material	Lifting force vertical to the surface, N, at vacuum level			Lifting force parallel to the surface, N, at vacuum level			Volume cm ³	Min. curve radius mm	Max. vertical movement mm	Weight rubber parts g
	20 -kPa	60 -kPa	90 -kPa	20 -kPa	60 -kPa	90 -kPa				
PU30°/60°	70	193	273	44	176	308	19	150	2	28
PU60°	82	231	330	47	113	169	19	150	2	53

Material specifications

Material	Colour	Hardness °Shore A	Temperature range °C
Polyurethane, PU30	Yellow	30	10–50
Polyurethane, PU60	Green transparent	60	10–50


Material resistance

Wear resistance	Oil	Weather & ozone	Hydrolysis	Petrol	Concentrated acids	Ethanol	Methanol	Oxidation
Excellent	Excellent	Excellent	Fair**	Fair	Fair**	Fair	Poor	Poor


**Please contact Piab.

Ordering information


	Complete suction cups	Art. No.
A	Suction cup F75P Polyurethane 30/60, 1/8" NPSF female, with mesh filter	0106349
A	Suction cup F75P Polyurethane 30/60, G3/8" female, with mesh filter	0106350
A	Suction cup F75P Polyurethane 30/60, 3/8" NPSF female, with mesh filter	0106351
A	Suction cup F75P Polyurethane 30/60, G1/2" female, with mesh filter	0106352
A	Suction cup F75P Polyurethane 60, 1/8" NPSF female, with mesh filter	0111585
A	Suction cup F75P Polyurethane 60, G3/8" female, with mesh filter	0111586
A	Suction cup F75P Polyurethane 60, 3/8" NPSF female, with mesh filter	0111587
A	Suction cup F75P Polyurethane 60, G1/2" female, with mesh filter	0111588
B	Suction cup F75P Polyurethane 30/60, thread insert G3/8" male, with mesh filter	0106830
B	Suction cup F75P Polyurethane 60, thread insert G3/8" male, with mesh filter	0107321
C	Suction cup F75P Polyurethane 30/60, 3/8" NPSF female	0108800
C	Suction cup F75P Polyurethane 60, 3/8" NPSF female	0108801



<Picture_Text changed="2004-04-27 16:20:44">A



<Picture_Text changed="2004-04-27 16:21:18">B




<Picture_Text changed="2004-08-24 14:43:14">C

	Rubber parts	Art. No.
A	Suction cup F75P Polyurethane 30/60	0104724
A	Suction cup F75P Polyurethane 60	0111584
B	Suction cup F75P Polyurethane 30/60, for tread insert	0106829
B	Suction cup F75P Polyurethane 60, for tread insert	0107320



<Picture_Text changed="2004-04-27 16:24:05">A



<Picture_Text changed="2004-04-27 16:24:42">B

	Fittings	Art. No.
	Fitting 75, G3/8" female, with mesh filter	0100551
	Fitting 75, 1/8" NPSF female, with mesh filter	0100548
	Fitting 75, G1/2" female, with mesh filter	0100555
	Fitting 75, 3/8" NPSF female, with mesh filter	0100553
	Thread insert G3/8" male, with O-ring and mesh filter	0107148