Suction cups/grippers DURAFLEX® Single and dual



FC25P



- Suitable for lifting small objects and narrow parts, also slightly domed, flat and oily surfaces, e.g., such as those encountered when handling steel sheets in press processes.
- Thanks to the high friction of the rubber material, the suction cups can withstand high forces at rapid accelerations in horizontal directions, even on oily surfaces.
- ➤ The suction cups have cleats that prevent thin objects from being disfigured.
- ▶ DURAFLEX® suction cups manufactured in a specially developed material that features the elasticity of rubber and wear resistance of polyurethane. The material does not leave any marks on the objects handled.

Lifting forces & Technical data

	force vertica , N, at vacuu		Lifting force parallel to the surface, N, at vacuum level		Volume	Min. curve radius	Max. vertical movement	Weight rubber part	
20 -kPa	60 -kPa	90 -kPa	20 -kPa	60 -kPa	90 -kPa	cm³	mm	mm	g
8.0	20.0	27	9.0	12.0	18.0	3.0	45	4.0	3

Material specifications

Material	Colour	Hardness °Shore A	Temperature range °C		
Polyurethane, PU50	Blue transparent	50	10–50		

Material resistance

ſ	Wear resistance	Oil	Weather & ozone	Hydrolysis	Petrol	Concentrated acids	Ethanol	Methanol	Oxidation
	Excellent	Excellent	Excellent	Fair**	Fair	Fair**	Fair	Poor	Poor


^{**}Please contact Piab.

Suction cups/grippers DURAFLEX® Single and dual




Ordering information

ſ		Complete suction cups				
Ī	Α	Suction cup FC25P Polyurethane 50, M5 female	0106719			
I	В	Suction cup FC25P Polyurethane 50, G1/8" male, with mesh filter	0106721			
١	С	Suction cup FC25P Polyurethane 50, G1/8" male / M5 female, with mesh filter	0106720			







<Picture_Text changed="2004-04-27 16:42:59">A <Picture_Text changed="2004-04-27 16:43:18">B

<Picture_Text changed="2004-04-27 16:43:32">C

Rubber part	Art. No.
Suction cup FC25P Polyurethane 50	0104803



Fittings	Art. No.
Fitting M5 female	3250003
Fitting G1/8" male, with mesh filter	3250085
Fitting G1/8" male/M5 female, with mesh filter	0101152