

FC75P



Flat, concave suction cup with cleats

- Suitable for slightly domed and flat and oily surfaces, e.g., such as those encountered when handling steel sheets in press processes.
- Thanks to the high friction of the rubber material, the suction cups can withstand high forces at rapid accelerations in horizontal directions, even on oily surfaces.
- The suction cups have cleats that prevent thin objects from being disfigured.
- DURAFLEX® suction cups manufactured in a specially developed material that features the elasticity of rubber and wear resistance of polyurethane. The material does not leave any marks on the objects handled.

Lifting forces & Technical data

Material	Lifting force vertical to the surface, N, at vacuum level			Lifting force parallel to the surface, N, at vacuum level			Volume	Min. curve radius	Max. vertical movement	Weight with fitting
	20 -kPa	60 -kPa	90 -kPa	20 -kPa	60 -kPa	90 -kPa	cm ³	mm	mm	g
PU40°	73	157	215	107	200	230	30	78	6.5	45
PU60°	73	168	225	93	225	255	30	78	6.5	45

Material specifications

Material	Colour	Hardness °Shore A	Temperature range °C
Polyurethane, PU40	Red transparent	40	10–50
Polyurethane, PU60	Green transparent	60	10–50

Material resistance

Wear resistance	Oil	Weather & ozone	Hydrolysis	Petrol	Concentrated acids	Ethanol	Methanol	Oxidation
Excellent	Excellent	Excellent	Fair**	Fair	Fair**	Fair	Poor	Poor

**Please contact Piab.



Ordering information

	Complete suction cups		Art. No.
А	Suction cup FC75P Polyurethane 40, G3	0103294	
А	Suction cup FC75P Polyurethane 60, G3	0103296	
В	Suction cup FC75P Polyurethane 40, thr	0106959	
В	Suction cup FC75P Polyurethane 60, thr	0107303	
С	Suction cup FC75P Polyurethane 40, 3/8	0108796	
С	Suction cup FC75P Polyurethane 60, 3/8	0108797	
	<pre></pre>	Picture_Text changed="2004-04-28 10:52:56">B	<pre>3/8"-18NPSF 3/8"-18NPSF Ø 75 </pre>
	bber parts ction cup FC75P Polyurethane 40, for trea		Art. No.
	0106948		
Su	ction cup FC75P Polyurethane 60, for trea	ad insert	0107302
	Ø 75		
Fit			Art. No.