

P35



Suction cup with cellular rubber profile

- ▶ Suitable for irregular and rough surfaces.
- ▶ Use a ball joint if prone to bending.
- ▶ Available with adjustable support for handling thin material. Also suitable for applications requiring accurate positioning.
- ▶ Can also be equipped with a cone valve.

Lifting forces & Technical data

Lifting force vertical to the surface, N, at vacuum level			Lifting force parallel to the surface, N, at vacuum level			Volume	Min. curve radius	Max. vertical movement	Weight with fitting
20 -kPa	60 -kPa	90 -kPa	20 -kPa	60 -kPa	90 -kPa	cm ³	mm	mm	g
20.0	50	70	—	—	—	6.0	—	3.0	22

Material specifications


Material	Colour	Hardness °Shore A	Temperature range °C
Ethylene propylene, EPDM	Grey	—	-40-100

Material resistance


Wear resistance	Oil	Weather & Ozone	Hydrolysis	Petrol	Concentrated acids	Alcohol	Oxidation
Fair	Poor	Excellent	Good	Poor	Poor	Excellent	Excellent

Ordering information

	Complete suction cups	Art. No.
A	Suction cup P35 Ethylene propylene, 1/8" NPSF female	3350045
B	Suction cup P35 Ethylene propylene, 1/8" NPSF female, with cone valve	3350038
B	Suction cup P35 Ethylene propylene, 1/8" NPSF female, adjustable support with filter	3350035



<Picture_Text changed="2004-04-29 11:18:45">A



<Picture_Text changed="2004-04-29 11:19:26">B

	Rubber parts	Art. No.
	Suction cup P35 Ethylene propylene	3350023

	Fittings & accessories	Art. No.
	Fitting 1/8" NPSF female	3350100
	Adjustable support for P35, with filter	3350030
	Cone valve for P35 & P60	3350033