

U15



Universal suction cup

- ▶ Suitable for objects with flat or slightly curved surfaces.
- ▶ Also used for concave objects.

Lifting forces & Technical data

Lifting force vertical to the surface, N, at vacuum level			Lifting force parallel to the surface, N, at vacuum level			Volume cm ³	Min. curve radius mm	Max. vertical movement mm	Weight rubber part g
20 -kPa	60 -kPa	90 -kPa	20 -kPa	60 -kPa	90 -kPa				
3.5	8.4	11.0	3.5	5.4	5.9	0.50	8.0	1.5	0.70

Material specifications


Material	Colour	Hardness °Shore A	Temperature range °C
Chloroprene, CR	Black	50	-40–110
Silicone, SIL	Red	50	-40–200

Material resistance

Material	Wear resistance	Oil	Weather & ozone	Hydrolysis	Petrol	Concentrated acids	Alcohol	Oxidation
Chloroprene, CR	Excellent	Fair	Good	Good	Fair	Poor	Good	Good
Silicone, SIL	Good	Poor	Excellent	Fair	Poor	Poor	Good	Excellent


Ordering information

Complete suction cups	Art. No.
Suction cup U15 Chloroprene, M5 male	3150006
Suction cup U15 Silicone, M5 male	3150006S



<Picture_Text changed="2004-04-29 12:46:52">

Rubber parts	Art. No.
Suction cup U15 Chloroprene	3150118
Suction cup U15 Silicone	3150118S



<Picture_Text changed="2004-06-23 09:13:22">

Fittings	Art. No.
Fitting M5 male, 10-15	3107030