

## U6



### Universal suction cup

- Suitable for objects with flat or slightly curved surfaces.
- Also used for concave objects.

### Lifting forces & Technical data

Lifting force vertical to the surface, N, at vacuum level			Lifting force parallel to the surface, N, at vacuum level			Volume	Min. curve radius	Max. vertical movement	Weight rubber part
20 -kPa	60 -kPa	90 -kPa	20 -kPa	60 -kPa	90 -kPa	cm <sup>3</sup>	mm	mm	g
0.50	1.7	2.5	0.50	1.5	2.0	0.05	5.0	0.30	0.14

### Material specifications


Material	Colour	Hardness °Shore A	Temperature range °C
Chloroprene, CR	Black	50	-40–110
Silicone, SIL	Red	50	-40–200

### Material resistance

Material	Wear resistance	Oil	Weather & ozone	Hydrolysis	Petrol	Concentrated acids	Alcohol	Oxidation
Chloroprene, CR	Excellent	Fair	Good	Good	Fair	Poor	Good	Good
Silicone, SIL	Good	Poor	Excellent	Fair	Poor	Poor	Good	Excellent


## Ordering information

Complete suction cups	Art. No.
Suction cup U6 Chloroprene, M5 male	3150003
Suction cup U6 Silicone, M5 male	3150003S



<Picture\_Text changed="2004-04-29 12:34:01">

Rubber parts	Art. No.
Suction cup U6 Chloroprene	3150115
Suction cup U6 Silicone	3150115S



<Picture\_Text changed="2004-04-29 12:44:54">

Fittings	Art. No.
Fitting M5 male, 5-8	3107031