# Suction cup F40-2 Nitrile-PVC, 1/8" NPSF female, with cone valve, F40-2.30.04UV





- Suitable for flat objects.
- Good stability and little inherent movement.
- Recommended when the lifting force is parallel to the surface of the object.
- Cleats prevent thin, sensitive objects from being deformed and gives extra friction when the lifting force is parallel.

#### General

Curve radius	2.05 in
Movement, vertical max.	0.07 in
Application	Dry sheet metal
Material	Nitrile-PVC (NPV)
Suction cup model	F
Suction cup shape	Flat
Volume	0.29 in <sup>3</sup>
Weight	0.19 oz

#### **Fitting**

Fitting size	1/8"
Fitting style	Female
Fitting type	NPSF-thread
Fitting option	Cone valve

#### **Dimension**

Height	o.83 in
Outer diameter	1.65 in
Outer diameter, actuated	1.72 in

### Performance — lifting forces

	<u></u>	<b>_</b>
6 -inHg	4.5 lbf	3.37 lbf
18 -inHg	8.99 lbf	5.62 lbf
27 -inHg	11.2 lbf	6.74 lbf


### Material

	Nitrile-PVC (NPV)
Color	Black
Hardness	50 'Shore A
Temperature	32 – 194 °F

## Material resistance

	Nitrile-PVC (NPV)
Alcohol	••
Concentrated acids	•
Ethanol	N/A
Hydrolysis	**
Methanol	N/A
Oil	***
Oxidation	**
Gasoline	***
Wear resistance	***
Weather and ozone	••

### Dimensional drawings



# Spare parts

	Part no.
Fitting 1/8" NPSF female, 30-40, with cone valve	04UV
Suction cup F40-2 Nitrile-PVC	F40-2.30

### **Accessories**

	Part no.
Fitting 1/4" NPT male, with dual flow control valve	04DC
Fitting 1/4" NPT male, with mesh filter	04AC
Fitting 1/8" NPSF female, 30-40	04AA
Fitting 1/8" NPSF female, 30-40, PA	04CA
Fitting 1/8" NPSF female, 30-40, with dual flow control valve	04DA
Fitting 1/8" NPSF female, 30-40, with mesh filter	04AG
Fitting 3/8" NPT male, with dual flow control valve	04DE
Fitting 3/8" NPT male, with mesh filter	04AE
Fitting 5x1/8" NPSF female, 30-40	04AF
Fitting 5x1/8" NPSF female, 30-40, with dual flow control valve	04DF
Fitting G1/4" male, 30-40, with mesh filter	04AB
Fitting G1/4" male, 30-40, with dual flow control valve	04DB
Fitting G3/8" male, 30–40, with dual flow control valve	o4DD
Fitting G3/8" male, 30-40, with mesh filter	04AD
Suction cup F40-2 Silicone	F40-2.20