


Suction cup F50-2 Silicone, for fitting with cone valve, 31.50.241S



- Suitable for flat objects.
- Good stability and little inherent movement.
- Recommended when the lifting force is parallel to the surface of the object.
- Cleats prevent thin, sensitive objects from being deformed and gives extra friction when the lifting force is parallel.



General

Curve radius	2.17 in
Movement, vertical max.	0.09 in
Application	Dry sheet metal
Material	Silicone (SIL)
Suction cup model	F
Suction cup shape	Flat
Volume	0.61 in ³
Weight	0.49 oz

Dimension

Height	0.69 in
Outer diameter	2.09 in
Outer diameter, actuated	2.15 in

Performance — lifting forces

		
6 -inHg	8.09 lbf	5.4 lbf
18 -inHg	16.6 lbf	8.99 lbf
27 -inHg	21.6 lbf	11.2 lbf


Material

	Silicone (SIL)
Color	Red
Hardness	50 °Shore A
Temperature	-40 – 392 °F

Material resistance

	Silicone (SIL)
Alcohol	++
Concentrated acids	-
Ethanol	N/A
Hydrolysis	+
Methanol	N/A
Oil	-
Oxidation	+++
Gasoline	-
Wear resistance	++
Weather and ozone	+++

Dimensional drawings



Spare parts

	Part no.
Cone valve for F50-2	31.50.057

Accessories

	Part no.
Fitting G3/8" male, 50, with mesh filter and dual flow control valve	05DD
Fitting G3/8" male, 50, with mesh filter	05AD
Fitting G1/4" male, with dual flow control valve	05DB
Fitting G1/4" male, 50, with mesh filter	05AB
Fitting 5x1/8" NPSF female, 50, with dual flow control valve	05DF
Fitting 5x1/8" NPSF female, 50	05AF
Fitting 3/8" NPT male, with mesh filter	05AE
Fitting 3/8" NPT male, with dual flow control valve	05DE
Fitting 1/8" NPSF female, 50, with mesh filter	05AG
Fitting 1/8" NPSF female, 50, with dual flow control valve	05DA
Fitting 1/8" NPSF female, 50, with cone valve	05UV
Fitting 1/8" NPSF female, 50, PA	05CA
Fitting 1/8" NPSF female, 50	05AA
Fitting 1/4" NPT male, with mesh filter	05AC
Fitting 1/4" NPT male, with dual flow control valve	05DC