


Suction cup F75P Polyurethane 30/60, 3/8" NPSF female, with mesh filter, 0106351



- Suitable for flat and rough surfaces.
- Fair stability and little inherent movement.
- Recommended when the lifting force is parallel to the surface of the object.
- In the two-coloured suction cup the bellows and the sealing lip are of different hardnesses, which makes the suction cup strong and stable and, at the same time, soft and flexible.
- DURAFLEX® suction cups manufactured in a specially developed material that features the elasticity of rubber and wear resistance of polyurethane. The material does not leave any marks on the objects handled.

Общее

Curve radius	150 mm
Movement, vertical max.	2 mm
Применение	Присоски не оставляющие следов, Присоски для транспортировки металлических листов с сухой поверхностью
Материал	Полиуретан (PU30), Полиуретан (PU60)
Модель присоски	F
Форма	Присоски для плоских поверхностей
Объем	19 см ³
Weight	28 g

Фитинга

Размер креплений	1/8"
Конструкция фитинга	Внутренняя резьба
Конструкция фитинга	NPSF-резьба
Варианты фитингов	Сетка фильтра

Измерение

Высота	26 mm
Внешний диаметр	77 mm
Внешний диаметр, с сервоприводом	80 mm

Производительность — подъемная сила

		
20 -kPa	70 N	44 N
60 -kPa	193 N	176 N
90 -kPa	273 N	308 N


Материал

	Полиуретан (PU30)	Полиуретан (PU60)
Цвет	Желтый	Зеленый прозрачный
Жесткость	30 °Shore A	60 °Shore A
Temperature	10 – 50 °C	10 – 50 °C

Сопротивление материала

	Полиуретан (PU30)	Полиуретан (PU60)
Алкоголь	N/A	N/A
Концентрированные кислоты	+	+
Этанол	+	+
Гидролиз	+	+
Метанол	-	-
Масло	+++	+++
Окисление	-	-
Бензин	+	+
Износостойкость	+++	+++
Атмосферные условия и озон	+++	+++

Масштабные чертежи



Запчасти

	Номер изделия
Suction cup F75P Polyurethane 30/60	0104724
Fitting 75, 3/8" NPSF female, with mesh filter	0100553
Cone Valve for Fitting 75	0100729

Аксессуары

	Номер изделия
Thread insert G3/8" male, with O-ring and mesh filter	0107148
Suction cup F75P Polyurethane 60, for tread insert	0107320
Suction cup F75P Polyurethane 60	0111584
Suction cup F75P Polyurethane 30/60, for tread insert	0106829
Fitting 75, G3/8" female, with mesh filter	0100551
Fitting 75, G3/8" female, with cone valve	0100552
Fitting 75, G1/2" female, with mesh filter	0100555
Fitting 75, 1/8" NPSF female, with mesh filter	0100548