

# Suction cup F110P Polyurethane 30/60, G3/8" female, with mesh filter, 0106353



- Suitable for flat and rough surfaces.
- Fair stability and little inherent movement.
- Recommended when the lifting force is parallel to the surface of the object.
- In the two-coloured suction cup the bellows and the sealing lip are of different hardnesses, which makes the suction cup strong and stable and, at the same time, soft and flexible.
- DURAFLEX® suction cups manufactured in a specially developed material that features the elasticity of rubber and wear resistance of polyurethane. The material does not leave any marks on the objects handled.

## Общее

Curve radius	250 mm
Movement, vertical max.	4 mm
Применение	Прииски не оставляющие следов, Прииски для транспортировки металлических листов с сухой поверхностью
Материал	Полиуретан (PU30), Полиуретан (PU60)
Модель присоски	F
Форма	Прииски для плоских поверхностей
Объем	60 cm <sup>3</sup>
Weight	82 g

## Фитинга

Размер креплений	3/8"
Конструкция фитинга	Внутренняя резьба
Конструкция фитинга	G-резьба
Варианты фитингов	Сетка фильтра

## Измерение

Высота	36 mm
Внешний диаметр	115 mm
Внешний диаметр, с сервоприводом	119,6 mm

## Производительность — подъемная сила

		
20-kPa	167 N	149 N
60-kPa	432 N	441 N
90-kPa	591 N	617 N


## Материал

	Полиуретан (PU30)	Полиуретан (PU60)
Цвет	Желтый	Зеленый прозрачный
Жесткость	30 °Shore A	60 °Shore A
Temperature	10 – 50 °C	10 – 50 °C

## Сопротивление материала

	Полиуретан (PU30)	Полиуретан (PU60)
Алкоголь	N/A	N/A
Концентрированные кислоты	+	+
Этанол	+	+
Гидролиз	+	+
Метанол	-	-
Масло	+++	+++
Окисление	-	-
Бензин	+	+
Износостойкость	+++	+++
Атмосферные условия и озон	+++	+++

## Масштабные чертежи



## Запчасти

	Номер изделия
Suction cup F110P Polyurethane 30/60	0104725
Fitting 110 G3/8" female, with mesh filter	0100557

## **Аксессуары**

Номер изделия	
Suction cup F110P Polyurethane 60	0111593
Suction cup F110P Polyurethane 30/60, for thread insert	0106796
Suction cup F110P Polyurethane 60, for thread insert	0107322
Fitting 110, 3/8" NPSF female, with mesh filter	0100559
Fitting 110, G1/2" female, with mesh filter	0100561
Fitting 110, G1/2" female, with cone valve	0100563
Thread insert G3/8" male, with O-ring and mesh filter	0107148