# Suction cup B75-2 Nitrile-PVC with filter, G1/2" female, with mesh filter, 0101865



- Suitable for level adjustment. Several short bellows in one lifting device can handle objects with height differences and varying shapes, for example embossed or corrugated plates.
- Lifting movement to separate small and thin objects.
- Only lightweight objects should be handled when the lifting force is parallel to the surface of the object, in order to achieve good precision and safe lifting movement.

#### General

| Curve radius            | 40 mm   |
|-------------------------|---|
| Movement, vertical max. | 24 mm   |
| Application             | Plastic injection molded parts, Dry sheet metal |
| Material                | Nitrile-PVC (NPV)                               |
| Suction cup model       | В   |
| Suction cup shape       | Bellows   |
| Volume                  | 110 cm <sup>3</sup>                             |
| Weight                  | 35 g  |

#### **Fitting**

| Fitting size   | 1/2"        |
|----------------|-------------|
| Fitting style  | Female      |
| Fitting type   | G-thread    |
| Fitting option | Filter mesh |

#### Dimension

| Height         | 50 mm |
|----------------|-------|
| Outer diameter | 78 mm |

## ${\bf Performance-lifting\ forces}$

|         | <b>1</b> | <b>±</b> |
|---------|----------|----------|
| 20 -kPa | 74 N     | 62.4 N   |
| 60 -kPa | 167 N    | 122.4 N  |
| 90 -kPa | 226 N    | 154.1 N  |


#### Material

|             | Silicone (SIL) |
|-------------|----------------|
| Colour      | Red            |
| Hardness    | 50 °Shore A    |
| Temperature | -40 – 200 °C   |

## Material resistance

|                    | Silicone (SIL) |
|--------------------|----------------|
| Alcohol            | ++             |
| Concentrated acids | -              |
| Ethanol            | N/A            |
| Hydrolysis         | +              |
| Methanol           | N/A            |
| Oil                | -              |
| Oxidation          | +++            |
| Petrol             | -              |
| Wear resistance    | ++             |
| Weather and ozone  | +++            |

## Dimensional drawings



# Values specified in the data sheet are tested at:

| Room temperature       | (20°C [68°F] ± 3°C [5.5°F])              |
|------------------------|--|
| Standard atmosphere    | (101.3 [29.9 inHg] ± 1.0 kPa [0.3 inHg]) |
| Relative humidity      | 0-100%                                   |
| Compressed air quality | DIN ISO 8573-1 class 4                   |

## Spare parts

|  | Item no. |
|--|----------|
| Fitting 75, G1/2" female, with mesh filter | 0100555  |
| Suction cup B75-2 Nitrile-PVC with filter  | 0101942  |

### Accessories

|  | Item no. |
|--|----------|
| Filter D=80, 10 pcs, for B75-2                                   | 0201149  |
| Fitting 1/4" NPT female Al, with mesh filter & 10-32 addl. conn. | 0127821  |
| Fitting 1/8" NPSF female Al, with mesh filter                    | 0127819  |
| Fitting 75, 1/8" NPSF female, with mesh filter                   | 0100548  |
| Fitting 75, 3/8" NPSF female, with mesh filter                   | 0100553  |
| Fitting 75, G3/8" female, with mesh filter                       | 0100551  |
| Fitting G1/2" female Al, with mesh filter                        | 0127820  |
| Suction cup B75-2 Nitrile-PVC, with filter & washer              | 3150096P |
| Suction cup B75-2 Silicone with filter                           | 0101943  |
| Suction cup B75-2 Silicone, with filter & washer                 | 3150096S |