



Item no: 9909670

Suction cup F50-2 Silicone FCM, 1/4" NPT male, with mesh filter

The material used is food grade silicone material. It is free from colour pigments, approved by FDA (FDA 21 CFR 177.2600.) and meets EU's regulation EU 1935/2004.(FDA approved). The cup is soft and pliable and can operate at a wide temperature range.

- The silicone material complies with FDA 21 CFR 177.2600 & EU 1935/2004.
- Suitable for flat objects.
- · Good stability and little inherent movement.
- Recommended when the lifting force is parallel to the surface of the object.
- Cleats prevent thin, sensitive objects from being deformed and gives extra friction when the lifting force is parallel.

General

Application Food contact materials (FDA & EU), non-detectable

Suction cup shape Flat

Material Silicone (SIL FDA)

Suction cup model F
Weight 14 g
Volume 10 cm³
Suction cup model F50-2
Movement, vertical max. 2.2 mm
Curve radius, min. 55 mm

Fitting

Fitting option Filter mesh
Fitting size 1/4"
Fitting style Male
Fitting type NPT-thread

Dimension

Height 32.5 mm Outer diameter 53 mm

Performance - lifting forces


	F50-2	Å	$\stackrel{\Rightarrow}{\bigtriangleup}$
20 -kPa		36 N	24 N
60 -kPa		74 N	40 N
90 -kPa		96 N	50 N


Material

Name	SILFDA
Colour	Transparent
Temperature	-40 - 200 °C
Hardness	50 °Shore A

SILFDA Alcohol ++ Concentrated acids Ethanol n/a Hydrolysis + Methanol n/a Oil Oxidation +++ Petrol Wear resistance ++ Weather and ozone +++

Dimensional drawings \triangle





Values specified in the data sheet are tested at:

- Room temperature: (20°C [68°F] ± 3°C [5.5°F])
- Standard atmosphere: (101.3 [29.9 inHg] ± 1.0 kPa [0.3 inHg])
- Relative humidity: 0-100%
- Compressed air quality: DIN ISO 8573-1 class 4

Accessories

0101154 Fitting 1/8" NPSF female, 50, with mesh filter
3250092 Fitting G1/4" male, 50, with mesh filter

Spare parts

3250094 Fitting 1/4" NPT male, with mesh filter
0200438 Suction cup F50-2 Silicone FCM